



Holland Shielding Systems BV

P.O. Box 730
3300 AS Dordrecht
The Netherlands

Jacobus Lipsweg 124
3316 BP Dordrecht

Phone +31 (0)78 - 613 13 66
Fax +31(0)78 - 614 95 85

ABN/AMRO bank 49.55.86.625

K.v.K. nr 23057218

BTW/VAT nr. NL804.474.096.B01

E-mail: info@hollandshielding.com
Internet: www.hollandshielding.com
www.faradaycages.com

Safety Sheet

Conductive Coating 3800 Series

Nickel/Acrylic conductive Coating

Nickel Acrylic Paint, cost effective, also available in aerosol for prototype and small runs.

Safety Precautions

Harmful by inhalation – do not breathe vapour if not enough ventilation, wear respiratory equipment avoid contact with skin and eyes, keep away from sources of ignition – no smoking.

Emergency action

Spillage

Absorb in earth or sand. Dispose in a safe way as for flammable solid.
Prevent liquid entering sewers, basements and work pits: vapour may create explosive atmosphere.
If substance has entered a water course or sewer or contaminated soil or vegetation, advise police.

Fire

Use water spray to cool containers.
Extinguish with dry chemical, foam, CO₂ or Sand.
Do not use Waterjet.

First Aid

Remove contaminated clothing immediately. Wash affected skin with soap and water.
If substance has got into eyes – immediately wash out with plenty of water for at least 15 minutes.
In case of skin contact – wash with soap and water.
For excessive vapour inhalation – remove to fresh air and seek medical attention.